



TURMOFLUID ED 13



Date of issue: 26.11.2024

TURMOFLUID ED 13 is a synthetic lubricant for multipurpose use with good spreading effect.

A special combination of substances enables lubrication also on humid metal parts.

Special properties

- Excellent dewatering properties
- Very good creeping ability
- High metal affinity
- Excellent corrosion protection
- Silicone-free

Product Characteristics	Value	Dimension	Norm / Standard
Colour	light yellow		
Density at 20°C	0,88	g/cm ³	DIN 51757
Operating temperature range	-45 to 150	°C	
Oil type	Synthetic Hydrocarbons		
Kinematic viscosity at 40°C	22	mm ² /s	DIN EN ISO 3104
Kinematic viscosity at 100°C	4,1	mm ² /s	DIN EN ISO 3104
Viscosity index (VI)	78		DIN ISO 2909
Pour point	-50	°C	DIN EN ISO 3016

Application

TURMOFLUID ED 13 is universally used for the lubrication of machines, as well as machine parts and chains of the control and measurement techniques, in the machine and tool manufacturing industry, as well as in the food and plastic industry.

Packaging units

12 x 400 ml spray cans, 6 x 1 l bottles, 5 l canister, 20 l canister, 60 l drum, 200 l drum

The products are subject to continuous strict production controls and comply with our own factory specifications. A warranty for each case cannot be given, due to the variety of relevant factors. Therefore, we recommend the implementation of field tests. Herewith, any liability is expressly excluded.

LUBRICANT CONSULT GMBH · Gutenbergstrasse 13 · 63477 Maintal (Germany)
Tel: +49 (0) 6109 / 7650-0 · Fax: +49 (0) 6109 / 7650-51 · E-Mail: webmaster@lubcon.com · Internet: <http://www.lubcon.com>